

TIMBERLINK.
MADE OF TASMANIA.



Timberlink Decking and Screening

Made here in Tasmania from Tasmanian grown renewable pine and dressed smooth on both sides, Timberlink decking is suitable for building decks and outdoor screens. It can be painted, stained or oiled to suit any style of garden.

Suitable Uses

Outdoor plantation decking is treated to hazard level H3. This means it is suitable for outdoor above ground applications but cannot be used in direct contact with the ground. For in-ground contacts choose H4 treated timber.

Guaranteed Durability

You can be confident that your outdoor pine deck will last as all our decking products are guaranteed for 15 years by a chemical supplier guarantee.

Sustainably Sourced Tasmanian Pine

At Timberlink Bell Bay we manufacture all our pine decking from Tasmanian grown plantation pine.

Cost-Effective

Australian pine is the economical option for building with as it grows quickly and is easy to manufacture into a wide variety of products. Outdoor pine decking also comes in a variety of lengths so you can minimize waste and save even more money.

Range

| Sizes (mm) | 90 x 22, 70 x 22 |
|-------------|-----------------------------------|
| Lengths (m) | 2.4, 3.0, 3.6, 4.2, 4.8, 5.4, 6.0 |

INSTALLATION INFORMATION

Bearers and Joists

Timberlink Green treated pine bearers and joists are recommended to provide a durable stable platform for your deck

Resealing

Where treated wood products are cut, notched, drilled or rebated the exposed areas must be coated with a suitable resealing product to ensure that a treatment envelope is maintained

Finishes

To prolong the life of your deck, it is strongly recommended that all treated wood products installed in weather exposed situations are stained, painted or oiled to maintain optimum serviceability, appearance and dimensional stability

Fixings

Galvanised decking nails or decking screws should be used along with corrosion resistant hot dip galvanised fasteners and connectors. For decks built in harsh environments such as close to the beach stainless steel fixings should be used.

Treatment Brand

Timberlink Bell Bay decking is treated with a non-CCA chemical in accordance with Australian Standards. The treatment brand is printed on the non graded face of the board. This brand (as shown on right) identifies:



- a) Producer (first 3 digits)
- b) Preservative (middle 2 digits)
- c) Treatment level (H3)

Safety

When handling and cutting any timbers it is advisable to wear dust masks, goggles and gloves. Do not burn any treated timber.