

TIMBERLINK[®] GREEN

PICKET FENCING

For the Australian home

NEW



Primed and ready for top coat

LOSP treatment for above ground outdoor use

Primed with Dulux[®] pre-primer

Made in Australia from renewable Plantation pine

TIMBERLINK[®]
Australia & New Zealand

TIMBERLINK[®] GREEN

Product Specification

These pickets have been protected with Dulux[®] pre-primer. You now only need to apply the final topcoat; which will save you time and money!

Manufactured according to Australian and New Zealand Standard AS/NZS 1604.1, with registered treatment brand:

854 64 H3

Product Installation

Resealing Requirements

All cut ends, notches, rebates and drill holes must be resealed with a suitable resealing product, to ensure a treatment envelope is maintained. We recommend Tanalised[®] Ecoseal, allowing 2 days to dry before final topcoat.

Preparation

Clean the surface so that it is free of all dirt, dust and grease. For further information refer to coating manufacturer's instructions prior to topcoating.

Recommended Topcoat instructions

To fully protect your pickets, we recommend applying 2-3 topcoats of quality paint including ends.

Sizes (mm)	70mm x 19mm
Lengths (m)	0.9, 1.2, 1.5, 1.8
Hazard Class	H3 above ground outdoor use
Appearance Grade	Tight knot
Coating	Dulux [®] pre-primer
Finish	DAR (Dressed All Round), smooth finish
Species	Radiata Pine

H3 treated for:



Termite Protected



Anti-fungal



Above Ground
Outdoor



timberlinkaustralia.com.au