

# TIMBERLINK<sup>®</sup> GREEN

## DECKING

### Treated Pine Decking



100% Renewable Plantation Pine

For use in outdoor, above ground applications (H3)

Lightweight for easy application

Can be easily painted or stained to fit your project colour scheme

TIMBERLINK<sup>®</sup>  
Australia & New Zealand

# TIMBERLINK<sup>®</sup> GREEN

## Gap

For Dry Decking, i.e. LOSP, we recommend a 5mm gap between boards. For Wet Decking, i.e. Tan E, we recommend no gap between decking boards, to allow for shrinkage as the boards dry.

## Which side up

Timberlink decking comes with a smooth side and a reeded side. It comes down to personal preference which side you would like facing up though reeded side down does reduce dirt build-up helping to prolong the life of the deck.

## Fixings

Galvanised decking nails or decking screws should be used. In harsh environments stainless steel fixings may be required.

## Finishes

It is strongly recommended that all timber decking is stained or painted with a suitable outdoor decking finish. If left unfinished timber exposed to the weather will fade to a silver grey colour and will develop splitting and surface checking.

## Resealing

When cut, notched, drilled or rebated the exposed areas of treated timber should be resealed with a suitable resealing product to ensure a treatment envelope is maintained.

## Treatment

All Timberlink decking is treated with a non-CCA chemical. Treatment chemical used can vary by state. All meet the relevant Australian Standards.

<b>Sizes (mm)</b>	90 x 22, 70 x 22 (also suitable for screening)
-------------------	--

<b>Lengths (m)</b>	1.8, 2.4, 3.0, 3.6, 4.2, 4.8, 5.4, 6.0
--------------------	--

Note: Not all sizes and lengths available all states.

